

## GFCI In-Line Cord Sets

Excellent for industrial plant maintenance, equipment service and construction site applications. Provides compliance with National Electric Code (NEC 2008) Article 590.6 for "Temporary Installations". Applications include:

- ▶ High Pressure Sprayer Washers
- ▶ Drain Snakes
- ▶ Construction Sites
- ▶ Construction Site Power Tools
- ▶ Pumps
- ▶ Industrial Appliances

Rainproof rated, UL listed for outdoor use. Standard Lengths: 2', 6', 25', 50'  
Custom cable gauges, lengths and terminations available by special order. To prevent unmonitored equipment startup, manual reset is required after GFCI trip and power outage.

### FEATURES

**25080-011(2')** ⓘ

**25080-016(6')**

**25080-025(25')**

- ▶ Volts /Amps: **120V/20A**
- ▶ Cord Gauge: 12/3 AWG.
- ▶ NEMA 5 - 20 P & R (yellow)
- ▶ Trip Level: 4 - 6 mA

**26020-002(2')** ⓘ

**26020-007(6')**

**26020-124(25')**

**26020-050(50')**

**26020-099(100')**

- ▶ Volts /Amps: **120V/15A**
- ▶ Cord Gauge: 14/3 or 12/3 AWG.
- ▶ NEMA 5 - 15 P & R (black)
- ▶ Trip Level: 4 - 6 mA
- ▶ Also available in 100' length
- ▶ Also available with lighted receptacle

**25090-001(2')** ⓘ

**25090-006(6')**

**25090-025(25')**

- ▶ Volts /Amps: **240V/15A**
- ▶ Cord Gauge: 14/3 AWG.
- ▶ NEMA 6 - 15 P & R (yellow)
- ▶ Trip Level: 4 - 6 mA

**26000-011(2')** ⓘ

**26000-016(6')**

**26000-125(25')**

- ▶ Volts /Amps: **240V/20A**
- ▶ Cord Gauge: 12/3 AWG.
- ▶ NEMA 6 - 20 P & R (black)
- ▶ Trip Level: 4 - 6 mA



### TECHNICAL DATA

Grounded Neutral	4 Ohms typical
Trip response time for ground fault and grounded neutral trip	less than 25mS
Voltage surge withstand	3kv ringwave test and 4kv/2kA surge immunity test
Radio frequency noise susceptibility	operates within normal limits with 0.5 volts injected on power line 150kHz-230mHz
Frequency	50 / 60 Hz
Endurance	3,000 operations minimum
Overload Current	six times rated current
Operating temperature range	-35°C to 66°C
Effect of 10 Amp turn DC Shock on ground fault trip	5% maximum trip level variation
Insulation voltage	1500 VRMS - 1 Min.
Power On indication	lighted indicator

